

Hydraulic Breakers ES Range

Slim shape, simple design and reliable performance for your day-to-day construction, gardening, landscaping and renovation jobs.



Epiroc



BA BREAKERS &
ATTACHMENTS



Epiroc



Atlas Copco


PART OF THE ATLAS COPCO GROUP

Technical specifications

Technical data		ES 60	ES 70	ES 80
Carrier weight class ¹	t	3-6	4-9	5-12
Service weight ²	kg	215	295	375
Tool diameter	mm	60	70	80
Maximum hydraulic input	kW	14	18	23
Oil flow rate	L/min	35-60	45-75	60-90
Operating pressure	bar	110-140	110-140	120-150
Impact rate	bpm	520-1,300	530-1,200	530-1,000
A	mm	785	851	928
B	mm	360	410	475

¹ Weights apply to standard carriers only. Any variances must be agreed with Epiroc and/or the carrier manufacturer prior to attachment.

² Breaker and breaker box with standard adapter plus working tool.



Solid Body concept

A solid block of special casted material eliminates the need for a separate guiding system and reduces the total number of parts compared to conventional hydraulic breakers

Hybrid technology

Integrated nitrogen piston accumulator for constantly high impact energy, safe start-up and smooth operation

Advanced control technology

The integrated control valve optimizes efficiency; the EnergyRecovery system increases operating efficiency and lowers vibrations

Field replaceable bushing

Full length floating tool bushing for quick exchange with standard hand tools

United in performance. Inspired by innovation.

Performance unites us, innovation inspires us, and commitment drives us to keep moving forward. Count on Epiroc to deliver the solutions you need to succeed today and the technology to lead tomorrow.
epiroc.com



PART OF THE ATLAS COPCO GROUP



Western Australia:

☎ +61 8 9248 9800
📠 +61 8 9209 3697

33-37 Denninup Way
Malaga, Perth
WA 6090

Queensland & NT:

☎ +61 7 3635 7333
📠 +61 7 3635 7355

76 Dulacca Street
Acacia Ridge, Brisbane
QLD 4110

WWW.BAEG.COM.AU

sales@baeg.com.au