

# Excavator attachments

Demolition, recycling and earth-moving.  
Experience our Hydraulic Attachment Tools.



PART OF THE ATLAS COPCO GROUP

# Cutting edge

Our multi-purpose Combi Cutters with various jaw type options can be used flexibly in primary demolition and secondary reduction of concrete structures as well as cutting steel structures at demolition sites.

360° endless hydraulic rotation allows optimal positioning and precise handling.

Faster working cycles thanks to the integrated speed valve.


Full hydraulic cylinder protection thanks to the piston rod guards.

CAPS, the Coupling and Positioning System, makes it easy to switch jaw types on site to suit the work in hand.




Crushing teeth of U-version are replaceable.

Cutting blades of the U- and S-versions are both replaceable and reversible.




Two powerful hydraulic cylinders deliver virtually constant closing force for high productivity.



Our highly dependable and versatile Combi Cutters feature two powerful hydraulic cylinders for superior productivity.


Two independently moving jaws eliminate displacement force, thus lowering stress levels.




## CC range

| Carrier weight class <sup>1)</sup> | t | CC 1700 | CC 2500 | CC 3700 | CC 5000 | CC 7000 |
|------------------------------------|---|---------|---------|---------|---------|---------|
| Universal version (U)              |   | 15 - 25 | 22 - 35 | 32 - 50 | 45 - 65 | 58 - 85 |

### Universal version (U)

|                                                                                       |                              |    |       |       |       |       |       |
|---------------------------------------------------------------------------------------|------------------------------|----|-------|-------|-------|-------|-------|
|  | Service weight <sup>2)</sup> | kg | 1,900 | 2,840 | 3,700 | 5,050 | 7,100 |
|                                                                                       | Product weight               | kg | 1,760 | 2,610 | 3,400 | 4,730 | 6,450 |
|                                                                                       | A                            | mm | 2,044 | 2,260 | 2,420 | 2,960 | 3,100 |
|                                                                                       | B                            | mm | 740   | 860   | 1,000 | 1,300 | 1,400 |
|                                                                                       | C                            | mm | 615   | 725   | 765   | 1,090 | 1,150 |
|                                                                                       | D                            | mm | 350   | 350   | 525   | 525   | 525   |
|                                                                                       | F1                           | t  | 225   | 370   | 510   | 620   | 830   |
|                                                                                       | F2                           | t  | 57    | 90    | 126   | 155   | 180   |

### Steel cutting version (S)


|                                                                                       |                              |    |       |       |       |       |       |
|---------------------------------------------------------------------------------------|------------------------------|----|-------|-------|-------|-------|-------|
|  | Service weight <sup>2)</sup> | kg | 1,750 | 2,550 | 3,400 | 4,830 | 6,750 |
|                                                                                       | Product weight               | kg | 1,610 | 2,340 | 3,110 | 4,510 | 6,000 |
|                                                                                       | A                            | mm | 1,868 | 2,095 | 2,320 | 2,800 | 2,930 |
|                                                                                       | B                            | mm | 370   | 400   | 440   | 720   | 750   |
|                                                                                       | C                            | mm | 430   | 460   | 625   | 865   | 900   |
|                                                                                       | D                            | mm | 380   | 380   | 525   | 875   | 875   |
|                                                                                       | F1                           | t  | 225   | 370   | 510   | 620   | 830   |
|                                                                                       | F2                           | t  | 79    | 130   | 147   | 198   | 205   |

### Universal & Steel cutting version

|                              |       |           |           |           |           |           |
|------------------------------|-------|-----------|-----------|-----------|-----------|-----------|
| Cycle time (opening/closing) | sec   | 17 / 16   | 31 / 29   | 3.0 / 2.8 | 3.7 / 3.2 | 3.7 / 3.7 |
| Oil flow rate                | l/min | 150 - 250 | 150 - 250 | 220 - 350 | 350 - 450 | 450 - 550 |
| Max. operating pressure      | bar   | 350       | 350       | 350       | 350       | 350       |
| Oil flow rate                | l/min | 35 - 50   | 35 - 50   | 35 - 50   | 45 - 55   | 45 - 55   |
| Max. operating pressure      | bar   | 170       | 170       | 170       | 115       | 115       |



<sup>1)</sup>Weights apply to standard carriers only. Any variances must be agreed with Epiroc and/or the carrier manufacturer prior to attachment.

<sup>2)</sup>Attachment with average-sized adapter plate.







**Western Australia:**

 +61 8 9248 9800  
 +61 8 9209 3697

71 Prestige Parade  
Wangara, Perth  
WA 6065

**Queensland & NT:**

 +61 7 3635 7333  
 +61 7 3635 7355

76 Dulacca Street  
Acacia Ridge, Brisbane  
QLD 4110

**WWW.BAEG.COM.AU**

[sales@baeg.com.au](mailto:sales@baeg.com.au)

**United in performance.  
Inspired by innovation.**

Performance unites us, innovation inspires us, and commitment drives us to keep moving forward. Count on Epiroc to deliver the solutions you need to succeed today and the technology to lead tomorrow.  
**epiroc.com**



**PART OF THE ATLAS COPCO GROUP**